STUDENT AWARDS





PARKING AND ELECTRIFICATION

CAR PARK POWER PLANT





INTRODUCTION PARKING DEMAND PARKING CHOICE BEHAVIOUR PARKING AS MOBILITY TOOL PARKING AND ELECTRIFICATION

Student information Author: Jurriaan Coomans Institution: Delft University of Techonology Graduation year: 2015

Exploring the operation of a Car Park Power Plant - Formalising the operation of a system innovation with the Actor-Option Framework

The Car Park Power Plant (CPPP) concept is in its essence a parking garage in which parked fuel cell vehicles (FCVs) are used for the generation of electricity.

On-site hydrogen production

By including on-site hydrogen production methods, the CPPPs could purchase electricity when it is cheap, store it, and convert it back to electricity when the electricity price is high.

System innovations such as the CPPP concept lead to large scale changes in infrastructure systems such as the electricity and the passenger transport infrastructure.

The infrastructural systems are complex systems in which designers of new elements are unable to control the use of these elements once deployed.

Knowledge is currently lacking concerning the influence of CPPP design choices and environmental uncertainties, on the possible future operational performance of the installation.

In order to aid in the delineation of the possible design space of CPPPs, we have set the objective of providing an approach that is capable of identifying possible barriers for the successful operation of a CPPP. To structure our research we have used the following research question:

Which Car Park Power Plant design elements or environmental factors could form barriers for the successful operation of an introduced CPPP installation?

To answer this question a literature study was conducted to find an appropriate theory to guide the identification of a relevant but delineated system representation. The Actor Option Framework was selected to serve this purpose.

Six factors form possible barriers

T

L

The system delineation was used to construct an agent based model that has been explored for possible behaviours of the CPPP and its surroundings. With the aid of the model we identified six factors that in sets of three form possible barriers for a successful operation of a CPPP:

- I The usage of simple CPPP operation tactics will result in CPPPs to produce electricity at all moments that satisfy the selected use-case. As a result the CPPP desires to produce electricity during many hours of the day.
 - FCVs are expected to have production capacities of around 100 kW. If the conversion efficiencies of FCVs remain in the range of what they are now, the FCVs could require an amount of hydrogen per hour that comes close to the daily capacities of today's on-site hydrogen production devices. Combined with the desire to produce electricity during many hours a day, an unsatisfiable hydrogen demand and a continuous hydrogen production emerges.
 - Without the possibility to determine profitable hours of hydrogen production, the possibility of making use of the price differences of electricity during a day will no longer be present. As a result the value of storage becomes too small to compensate for the conversion losses within the CPPP. In these cases the CPPP can be expected to

INTRODUCTION PARKING DEMAND PARKING CHOICE BEHAVIOUR PARKING AS MOBILITY TOOL PARKING AND ELECTRIFICATION

make operational losses due to the absence of a positive profit margin.

- I Choosing to reward motorists who park at a CPPP with a free refill of hydrogen is unlikely to have significant effects on their perceptions. Due to the fact that FCVs consume a small amount hydrogen per driven kilometre, the perceived monetary value of the received free hydrogen is insufficient to structurally persuade motorists to park at the CPPP.
- Also the effect of the existence of a CPPP on the decision of a motorist with respect to the choice between purchasing an FCV or a conventional vehicle could be limited. Benefits that a CPPP could offer for FCV owners are a reduction in fuel costs and an improved environmental performance of their vehicle. The valuation of these benefits by motorists is however insignificant when compared to the valuation of the purchase price of vehicles.
- I If both the share of motorists with an FCV and the share of these motorists that park their car at a CPPP are low, the CPPP will have to rely on a very large motorist population. This would make it difficult to find a suitable location that such a large base population would consider to use as a daily parking location.

We observe that the approach as we have used it is capable of identifying possible operational barriers for CPPPs and possibly for system innovations in general.

The knowledge gained from this study can be used as a base to further explore the possible operation of CPPPs, as a base for discussion concerning possible CPPP designs or as substantiation for research towards the identified factors.



CHARGING EVS AT THE WORKPLACE

Student information Author: Dennis van der Meer Institution: Delft University of Technology Graduation year: 2016

Advancing sustainable transportation by charging EVs with PV power at the workplace: an optimal charging strategy

Arguably, the most important challenge of our time is climate change. In The Netherlands in 2014, 30% and 21.5% of total CO_2 emissions were emitted by the electricity producing and transportation sector, respectively.

Electric vehicles (EVs) have therefore gained interest as they do not emit carbon dioxide whilst driving and therefore do not pollute, at least directly.

Nevertheless, when EVs are charged with electricity produced by a fossil-fuel power plant there are indirect emissions. Additionally, high penetration of EVs will inevitably lead to increased stress on the grid and consequently capital expenditure.

A viable solution to mitigate both these disadvantages is by charging EVs at the workplace with locally produced photovoltaic (PV) power. The high level of coincidence between parking time and solar power paves way to charge EVs in a sustainable and cost-efficient manner.

Energy Management System

The thesis work presents the design of an energy management system (EMS) capable of forecasting PV power production and optimising power flows between PV system, grid and EVs at the workplace.

The aim is to reduce energy demand on the grid by increasing PV self-consumption while minimising charging costs and consequently increasing sustainability of the EV fleet.

The developed EMS consists of two components: an autoregressive integrated moving average (ARIMA) model to predict PV power production and a mixed integer linear programming (MILP) framework that optimally allocates power to minimise charging costs.

The EMS is designed such that it can be implemented in practice and moreover, is versatile, implying that it can be utilised for alternative purposes as well. Additionally, the predictive quality of the system enables it to anticipate and act accordingly, rather than solely react.

In order to perform sensitivity analyses, case studies will be formulated in which the effectiveness of the system can be ascertained.

The results show that the developed EMS is able to reduce charging costs significantly, while simultaneously increasing PV self-consumption and reducing energy demand from the grid.

Furthermore, during a case study analogous to one repeatedly considered in literature, i.e. dynamic grid tariff and dynamic feed-in tariff (FIT), the EMS reduces charging costs by 118.44% and 427.45% in case of one and two charging points, respectively.

Moreover, stress on the grid is alleviated through both load shifting and power injection during peak demand. In addition, the EMS proves that vehicle-to-grid (V2G) leads to optimality only in extraordinary cases.

The optimisation problem is modelled in GAMS, whereas the ARIMA process is modelled in Matlab and subsequently, the EMS is simulated in Matlab.